

HT Series | 1100Vdc

73-136kW | up to 12 MPPTs

Three Phase

The new HT 1100Vdc Series (73-136 kW) is GoodWe's new string inverter for C&I and small utility projects. The HT series offers up to 12 MPPTs, and is compatible with bifacial modules, with a higher threshold of DC current (Max. 15A per string). It includes PLC communication and internal humidity detection. The configuration can be easily done via Bluetooth and firmware diagnosis & upgrading can be done remotely. The HT series seamlessly incorporates different sets of technical strengths designed to achieve higher savings in the installation, enhance productivity and diversify available monitoring options, taking safety to the maximum possible level in accordance with the strictest industry standards. This inverter comes with an optional AC switch for reduced overall costs and reduced installation time. Configuration can be easily done via Bluetooth, and diagnosis and firmware upgrading can be operated remotely. This outstanding set of features was conceived to ensure the lowest levelized cost of electricity (LCOE).



Compatible with Bifacial Module



Power line communication



Easy and quick configuration via bluetooth



I-V curve diagnosis



Internal humidity monitoring

Technical Data	GW73KLV-HT	GW75K-HT	GW80K-HT	GW100K-HT	GW110K-HT	GW120K-HT	GW136K-HTH
Input							
Max. DC Input Power (kW)	112.5	112.5	120	150	165	180	205
Max. DC Input Voltage (V)	800	1100	1100	1100	1100	1100	1100
MPPT Operating Voltage Range (V)	180~650	180~1000	180~1000	180~1000	180~1000	180~1000	180~1000
Start-up Voltage (V)	200	200	200	200	200	200	200
MPPT Range for Full Load	200~650	500~850	500~850	500~850	500~850	500~850	500~850
Nominal Input Voltage (V)	370	600	600	600	600	600	750
Max. Backfeed Current to The Array (A)	0	0	0	0	0	0	0
Max. Input Current per MPPT (A)	30	30	30	30	30	30	30
Max. Short Circuit Current per MPPT (A)	45	45	45	45	45	45	45
Number of MPPTs	12	10	10	10	12	12	12
Number of Strings per MPPT	2	2	2	2	2	2	2
Output							
Nominal Output Power (kW)	73	75	80	100*1	110	120	136
Max. AC Active Power (kW)	73@220V; 69@208V; 75@230V	75	88	110	121	132	150
Rated Apparent Power (KVA)	73	75	80	100*1	110	120	136
Max. AC Apparent Power (kVA)	75	75	88	110	121	132	150
Nominal Output Voltage (V)	220V, 3L / N / PE or 3L / PE	380V / 400V, 3L / N / PE or 3L / PE			400V, 3L / N / PE or 3L / PE		500V, 3L / PE
Nominal AC Grid Frequency (Hz)	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60
Max. Output Current (A)	192	125.3	134	167	175.5	191.3	173.2
Max. Output Fault Current (peak and duration) (A)	364@5μs	364@5μs	364@5μs	364@5μs	364@5μs	364@5μs	364@5μs
Inrush Current (peak and duration) (A)	120@1μs	120@1μs	120@1μs	120@1μs	120@1μs	120@1μs	120@1μs
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)						
Max. Total Harmonic Distortion	<3%	<3%	<3%	<3%	<3%	<3%	<3%
Efficiency							
Max. Efficiency	98.4%	98.6%	98.6%	98.6%	98.6%	98.6%	99.0%
European Efficiency	98.1%	98.3%	98.3%	98.3%	98.3%	98.3%	98.5%
Protection							
PV String Current Monitoring	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Internal Humidity Detection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Insulation Resistance Detection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Anti-islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Surge Arrester	Type II (Type I optional)						
AC Surge Arrester	Type II (Type I optional)						
AC Overcurrent Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
AC Short Circuit Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
AC Overvoltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Arc Fault Circuit Interrupter	Optional	Optional	Optional	Optional	Optional	Optional	Optional
PID Recovery	Optional	Optional	Optional	Optional	Optional	Optional	Optional
General Data							
Operating Temperature Range (°C)	-30 ~ 60						
Relative Humidity	0~100%						
Max. Operating Altitude (m)	5000 (>4000 derating)						
Cooling Method	Smart Fan Cooling						
Display	LED, LCD (Optional), Bluetooth+APP						
Communication	RS485 / PLC / WiFi						
Weight (Kg)	98.5	93.5	93.5	93.5	98.5	98.5	98.5
Size (Width × Height × Depth mm)	1008 × 678 × 343						
DC Connector	MC4 (Max. 6 mm ²)						
AC Connector	OT / DT terminal (Max. 300 mm ²)						
Ingress Protection Rating	IP66						
Night Self Consumption (W)	<2						
Overvoltage Category	PVII / ACIII						
Protective class	I						
Noise Emission (dB)	<70						
Topology	Transformerless						

*1: For Australia Nominal Output Power and Rated Apparent Power: 99.99KW / 99.99KVA.
*: Please visit GoodWe website for the latest certificates.